

Hotrun X21



3-phase power supply only

Dimensions	315 x 204 x 130 mm	
Power rating	Programmable to 12, 15, 18 or 21 kWatt	
Voltage	3-phase 415 Volts	
Current	3x16, 20, 25 or 32 Amps	
IP rating	IP24	
Connection	1/2 BSP"	
Weight	6 kg	
Performance (at $\Delta T = 25^{\circ}\text{C}$)	Set to 12kW	Flowrate 7.4 L/min
	Set to 15kW	Flowrate 9.3 L/min
	Set to 18kW	Flowrate 11.4 L/min
	Set to 21kW	Flowrate 13.2 L/min
Inlet pressure rating	Working pressure up to 2 MPa, test pressure 3MPa	

Variable programmable power setting, 12, 15, 18 or 21 kWatt

Variable programmable temperature limiter can be set to any required temperature

Variable programmable temperature set-point by the end user (below limiter temperature)

Tip: Base your model selection on the Winter inlet water temperature

Tip: Position within 6 metres of outlet if possible to minimise legionella risk

Tip: Allow 50mm on sides for cord etc and 100mm under the bottom for water connections



Features

1. Pressure resistant up to 3MPa (leak free guarantee for 8 years)
2. Variable power supply selection (kW)
3. Remote life time monitoring and diagnostics for fault conditions
4. Highly energy efficient and will only use the exact amount of power required
5. Remote temperature control
6. Built in temperature limiter
8. Digital temperature control and display